

TACFLEX LIQUID TIGHT FLEXIBLE CONDUITS




FLEXIBLE SPIRAL CONDUITS STEEL WIRE OVER BRAIDING LIQUID TIGHT


TECHNICAL DETAILS

Material	: Galvanised steel PVC coated steel wire over braiding liquid tight
Certificates	: ROHS, CE, PT, TUV
Color	: Black Other color versions are available on request with reasonable qty.
Protection class	: IP66
Temperature range	: -20 °C + 100 °C

Properties

High impact strength
Self-extinguishing
High UV resistance (black)
High abrasion resistance
EMC screen

AĞIR HİZMET ÇELİK TEL ÖRGÜLÜ PVC KAPLI METAL SİRİAL BORULAR



Hammaddesi	: Galvaniz & kalay kaplı sac
1. Kaplama	: PVC
2. Kaplama	: Galvaniz / paslanmaz çelik
Sürekli ısıya direnci	: -20 °C + 100 °C
Özellik	: Alev iletmez UV dayanımlı Ağır hizmet tipi Kırılmayı önleyici mühür ipli EMC screen özelliği
Renk	: Gri / Siyah

PRODUCT RANGE OVERVIEW

Code	Size	d mm.		d1 mm.		Roll Length mt.
LGTCT 10	1/4"	10,3	10,5	17,5	18	30
LGTCT 12	3/8"	12,3	12,7	19,5	20	30
LGTCT 16	1/2"	15,5	16,3	22,8	23,4	30
LGTCT 21	3/4"	20,9	21,3	28,2	28,5	30
LGTCT 27	1"	26	27	34,7	35,3	30
LGTCT 35	1 1/4"	35	35,5	42,5	44	15
LGTCT 40	1 1/2"	40	40,5	49,3	50,2	15
LGTCT 51	2"	51,5	51,9	61,5	62	15
LGTCT 63	2 1/2"	63	63,5	74,2	75	7,5
LGTCT 78	3"	78	78,5	90	100,5	7,5
LGTCT 91	3 1/2"	88,9	89,9	102,6	103,6	7,5
LGTCT 102	4"	101,6	102,6	113,3	116,3	7,5