

TACFLEX POLYAMIDE V0 SPIRAL CONDUITS






PLASTIC SPIRAL CONDUITS PA 6 V0

TECHNICAL DETAILS

Material	: Polyamid PA6 V0
Certificates	: ROHS, CE, PT, TUV, DB Din 5510
Color	: Black (RAL9005)
	* Orange or any other color versions are available on request
Temperature range	: -40 °C + 120 °C
Flammability class	: UL94 V0

Properties

High fatigue life
High impact strength
Halogen free
Self-extinguishing
High abrasion resistance
High UV resistance (black)
Full-shrink packing



POLYAMİD V0 SİRAL BORU

Hammaddesi	: Polyamid PA6 V0
Renk	: RAL 9005 (Siyah)
Çalışma sıcaklığı	: -40 °C + 120 °C
Kullanım alanları	: Mekanik ve ekipman cihaz bağlantılarında makine, matbaa, otomotiv, lokomotif, tramvay, gemi otomatik makinaları, endüstriyel tesis montajlarında, aydınlatma ve elektrik pano montajlarında kullanılmaktadır.

PA6 SPIRAL CONDUITS

PRODUCT RANGE OVERVIEW

Nominal Diameter	Black Code ■ RAL 9005	d Ø mm.	d1 Ø mm.	Roll Length mt.	Halogen free
9	OSPA 9 V0	10	13	100	
11	OSPA 11 V0	12	15,8	50	
13,5	OSPA 13,5 V0	14,4	18,4	50	
16	OSPA 16 V0	16,5	21,2	50	
21	OSPA 21 V0	23,5	28,4	50	
29	OSPA 29 V0	29	34,5	25	
36	OSPA 36 V0	36	42,5	25	
48	OSPA 48 V0	48	54,5	25	