


TACFLEX POLYAMIDE SPIRAL CONDUITS



PLASTIC SPIRAL CONDUITS

PA 6

TECHNICAL DETAILS

Material : Polyamide PA6 V2
 Certificates : ROHS, CE, ECE R118
 Color : Gray (RAL7031) Black (RAL9005)
 * Orange or any other color versions are available on request
 Temperature range : -40 °C +120 °C
 Flammability class : UL94 V2

Properties
 High fatigue life
 High impact strength
 Halogen free
 Self-extinguishing
 High abrasion resistance
 High UV resistance (black)
 Full-shrink packing

PA6 SPIRAL CONDUITS

PRODUCT RANGE OVERVIEW

Nominal Diameter	Gray Code	Black Code	d Ø mm.	d1 Ø mm.	Roll Length mt.
	■ RAL 7031	■ RAL 9005			
7	OGPA 7	OSPA 7	6,5	10	100
8,5	OGPA 8,5	OSPA 8,5	8,5	12	100
9	OGPA 9	OSPA 9	10	13	100
11	OGPA 11	OSPA 11	12	15,8	50
13,5	OGPA 13,5	OSPA 13,5	14,5	18,4	50
16	OGPA 16	OSPA 16	17	21,2	50
19	OGPA 19	OSPA 19	19	24	50
21	OGPA 21	OSPA 21	23,2	28,4	50
26	OGPA 26	OSPA 26	26	31	50
29	OGPA 29	OSPA 29	29	34,5	25
36	OGPA 36	OSPA 36	36	42,5	25
48	OGPA 48	OSPA 48	48	54,5	25

Halogen free