

ORTAC METAL CABLE GLANDS SERIES



## METAL CABLE GLANDS FOR ARMoured CABLE BRASS


### TECHNICAL DETAILS

#### Material

Cap nut	: Brass with nickel plated
Ring	: Brass with nickel plated
Compression part	: Brass with nickel plated
Gland body	: Brass with nickel plated
O-ring	: NBR
Connection thread	: Metric (EN60423)
Certificates	: ROHS, CE, PT, TUV, TURK LOYDU
Protection class	: IP54
Temperature range	: -20 °C +100 °C -40 °C +150 °C

#### Properties

Ship building  
Off shore  
Wind power plant  
For armoured cables  
For wide cable range



### VG TİP TOPRAKLAMALI RAKOR

Hammaddesi	: Piring, nikel kaplı
Koruma sınıfı	: IP54
Isiya direnci	: -20 °C + 100 °C -40 °C + 150 °C
O-ring	: Nitril kauçuk
Norm	: VG 88812 VG 88773
Gövde Din normu	: 89280

### METRIC THREAD CABLE GLANDS

AG Thread	Code	GL mm	Ø mm	mm	mm
M 16 x 1,5	MACGN16A	9	20	20	10,5
M 18 x 1,5	MACGN18A	10	22	22	11,5
M 18 x 1,5	MACGN18B	10	22	22	11,5 - 12,5
M 24 x 1,5	MACGN24A	11	28	27	11,5
M 24 x 1,5	MACGN24B	11	28	27	11,5 - 13,5
M 24 x 1,5	MACGN24C	11	28	27	13,3 - 16,5
M 30 x 2,0	MACGN30A	12	35	32	16,5 - 18
M 30 x 2,0	MACGN30B	12	35	32	18 - 19,5
M 30 x 2,0	MACGN30C	12	35	32	19,5 - 20,5
M 36 x 2,0	MACGN36A	13	40	40	20,5 - 22,5
M 36 x 2,0	MACGN36B	13	40	40	22,5 - 25,5
M 45 x 2,0	MACGN45A	14	50	50	25,5 - 27,5
M 45 x 2,0	MACGN45B	14	50	50	27,5 - 31,5
M 56 x 2,0	MACGN56A	15	62	60	31,5 - 34
M 56 x 2,0	MACGN56B	15	62	60	34 - 37,5
M 56 x 2,0	MACGN56C	15	62	60	37,5 - 41
M 72 x 2,0	MACGN72A	16	78	75	41 - 46
M 72 x 2,0	MACGN72B	16	78	75	46 - 50,5

PRODUCT RANGE OVERVIEW