

WUG UNARMOURED CABLE GLANDS




INDUSTRIAL TYPE GLANDS



UNARMOURED CABLE GLANDS
WUG SERIES

TECHNICAL DETAILS

- Type : WUG (un-ar) armoured gland
- Certificate : Gost-CE-Rohs-ISO9001-14001-Ohsas 18001
ROHS, CE, PT, TUV
- Material : MS58 Brass with or without nickel plated
Stainless steel AISI303 / 316L / Aluminium
- Standards : EN 60079-0:2012, 60079-1:2007, 60079-31:2009
- Protection class : IP66 / 68
- Temperature : -30 °C +120 °C NBR
-40 °C +100 °C NEOPRENE
-60 °C +180 °C SILICONE
-30 °C +100 °C TPE/V
- Cable type : Unarmoured



PRODUCT RANGE OVERVIEW

Product Size	Product Code	Standard AG	AG NPT	B		GL min. mm	C	
				Min	Max		mm	B
16	WUGXX-16-X	M16x1,5	1/2"	6,1	11,6	15	20	20
20s	WUGXX-20s-X	M20sx1,5	1/2"	6,1	13,2	15	24	24
20	WUGXX-20-X	M20x1,5	1/2"	9,5	15,9	15	24	24
25	WUGXX-25-X	M25x1,5	3/4"	12,5	20,5	15	30	30
32	WUGXX-32-X	M32x1,5	1"	18,2	26,2	15	38	38
40	WUGXX-40-X	M40x1,5	1 1/4"	23,7	33,9	15	45	45
50	WUGXX-50-X	M50x1,5	1 1/2"	27,9	40,4	15	55	55
63s	WUGXX-63s-X	M63sx1,5	2"	40,4	51	15	70	70
63	WUGXX-63-X	M63x1,5	2 1/2"	47,2	55,9	15	70	70
75s	WUGXX-75s-X	M75sx1,5	2 1/2"	52,8	59	15	80	80
75	WUGXX-75-X	M75x1,5	3"	59,1	67,9	15	90	90