

ORTAC PLASTIC CABLE GLANDS SERIES



POLYAMIDE CABLE GLANDS SPIRAL TYPE


TECHNICAL DETAILS

Material

- Cap nut : Polyamide PA6 V2
- Sealing ring : TPV special seal for bend resistance
- Gland body : Polyamide PA6 V2
- Connection thread : PG (DIN 40430)
- Certificates : ROHS,CE,PT,TUV
- Protection class : IP68 - 5 bar (with o-ring)
- Temperature range : -20 °C +100 °C
-30 °C +150 °C (short term)

Properties

- With spiral top for bend protection
- For highly movable flexible cables
- Antivibration protection
- UV resistance (on request)
- Easy to assemble
- Halogen free



■ RAL 7001 ■ RAL 7035 ■ RAL 9005

PG THREAD CABLE GLANDS

AG Thread	Gray Code ■ RAL 7001	L. Gray Code ■ RAL 7035	Black Code ■ RAL 9005	H mm	GL mm	mm	mm
PG 7	ORG 19	ORL 19	ORB 19	57	8	15	3 - 6,5
PG 9	ORG 20	ORL 20	ORB 20	70	8	19	4 - 8
PG 11	ORG 21	ORL 21	ORB 21	81	8	22	5 - 10
PG 13,5	ORG 22	ORL 22	ORB 22	89	9	24	6 - 12
PG 16	ORG 23	ORL 23	ORB 23	107	9	27	10 - 14
PG 21	ORG 24	ORL 24	ORB 24	124	11	33	13 - 18

IP 68

Halogen free

LONG THREAD PG CABLE GLANDS

PG 7	ORG 19L	ORL 19L	ORB 19L	57	15	15	3 - 6,5
PG 9	ORG 20L	ORL 20L	ORB 20L	70	15	19	4 - 8
PG 11	ORG 21L	ORL 21L	ORB 21L	81	15	22	5 - 10
PG 13,5	ORG 22L	ORL 22L	ORB 22L	89	15	24	6 - 12
PG 16	ORG 23L	ORL 23L	ORB 23L	107	15	27	10 - 14
PG 21	ORG 24L	ORL 24L	ORB 24L	124	15	33	13 - 18

PRODUCT RANGE OVERVIEW